




KEY FEATURES

- Tapered angled design minimizes ligature risks
- Wheelchair accessible design
- Can be fixed to the wall at a height which suits the user
- Hygienic wipe-clean surface
- Strength and stability tested for severe contract use
- Polyethylene material is 100% recyclable
- 100% waterproof construction with hygienic wipe-clean surface



MATERIAL/FABRICATION

Rotationally molded, durable polyethylene, one-piece construction provides excellent strength and stability. Flamed, textured finish further strengthens the fire-retardant, water-resistant, UV-stabilized shell. Anti-microbial material gives high chemical resistance (e.g. ammonia, sodium hydroxide) throughout the product. Item is fully recyclable as polyethylene can be melted down to create a whole new product.

TEST STANDARDS

- EN 15372 non-domestic testing
- EN 15372:2016 Test Level 3

OPTIONS

- Optionally made with 40% reused content

COLOR/FINISH

CORE COLORS



NON-CORE COLORS



ASSEMBLY

Arrives assembled and ready to use

INSTALLATION/FITTING

Wall fixing solution - We recommend fitting to be completed by our skilled installation team. Otherwise products may be fixed, by the customer, using wall anchors and fixings of their choice.

MAINTENANCE

Avoid using abrasive materials or cleaning agents, solvents, steam cleaning or jet washing. Use bleach and chlorine disinfectant with caution and avoid placing in close proximity to sources of heat. Read more on our website.

WARRANTY

Lifetime guarantee against all manufacturing faults

DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape

Due to the nature of the rotational molding process, flat surfaces on Ryno® products may feature slight undulations which do not detract from the product's strength or durability.